



Rudarsko-geološko-građevinski fakultet Univerziteta u Tuzli
u saradnji sa
Društvom za geotehniku u Bosni i Hercegovini

Faculty of Mining, Geology and Civil Engineering, University of Tuzla
in co-operation with
Geotechnical Society in Bosnia and Herzegovina



GEO-EXPO 2012

Drugi međunarodni naučni skup: STANJE I PRAVCI RAZVOJA GRAĐEVINARSTVA – GTZ 2012
i
Drugo savjetovanje GEO-EXPO 2012

2nd International Scientific Meeting: STATE AND TRENDS OF CIVIL ENGINEERING – GTZ 2012
and
2nd Conference GEO-EXPO 2012

UREDNICI/ EDITORS
A. Ibrahimović, D. Zenunović

ZBORNIK RADOVA/ PROCEEDINGS
1. DIO
Tuzla, 7 - 9 juni/ June 2012.

Urednici/ Editors:
Dr.sc.-Dipl.ing. Adnan Ibrahimović, docent
Dr.sc.-Dipl.ing. Damir Zenunović, docent

Nacionalna i univerzitetska biblioteka
Bosne i Hercegovine, Sarajevo

624(497.6)"2012"(082)

DRUGI međunarodni naučni skup Stanje i pravci
razvoja građevinarstva - GTZ 2012 i Drugo
savjetovanje GEO-EXPO 2012 : zbornik radova = 2nd
international scientific meeting State and Trends
of civil engineering GTZ 2012 and 2nd Conference
GEO-EXPO 2012 : proceedings / urednici, editors A.
Ibrahimović, D zenunović. - Tuzla :
Rudarsko-geološko-građevinski fakultet : In scan,
2012. - 1154 str. : ilustr. ; 25 cm

Bibliografija i bilješke uz tekst

ISBN 978-9958-628-16-0

1. Up. stv. nasl.

COBISS.BH-ID 19584518

Međunarodni naučni skup GTZ 2012 i Savjetovanje GEO-EXPO 2012
Internacional scientific meeting GTZ 2012 and Conference GEO-EXPO 2012

Tehnički organizatori skupa i savjetovanja: Rudarsko-geološko-građevinski fakultet Tuzla i
Društvo za geotehniku u Bosni i Hercegovini
Technical organizers of the meeting and conference: Faculty of Mining, Geology and Civil
Engineering and Geotechnical Society in Bosnia and Herzegovina

Tehnički urednik Zbornika radova/ Technical editors of Proceedings:

Edhem Šljivić

Izdavač:

Rudarsko-geološko-građevinski fakultet Tuzla i In scan d.o.o. Tuzla

Publisher:

Faculty of Mining, Geology and Civil Engineering and In scan d.o.o. Tuzla

Štampa/Printing:

IN SCAN d.o.o. Tuzla

Tiraž/No. of copies:

200

Medunarodni naučni odbor/International Scientific Committee

Prof. Dr. Miha Tomažević

Prof. Dr. Branislav Verbič

Prof. Dr. Enver Mandžić

Prof. Dr. Ibrahim Jašarević

Prof. Dr. Radomir Folić

Prof. Dr. Dubravka Bjegović

Prof. Dr. Ludvik Trauner

Prof. Dr. Tarik Kupusović

Prof. Dr. Marko Ivetić

Prof. Dr. Danilo Ristić

Prof. Dr. Uwe Dorka

Prof. Dr. Lidija Krstevska

Prof. Dr. Ibrahim Čačković

Prof. Dr. Milan Stević

Prof. Dr. Zijad Pašić

Prof. Dr. Petar Brana

Prof. Dr. Azra Kurtović

Prof. Dr. Esad Mešić

Prof. Dr. Damir Markulak

Prof. Dr. Vlastimir Radonjanin

Prof. Dr. Violeta Mirčevska

Ljubljana, Slovenija

Sarajevo, Bosna i Hercegovina/Bosnia & Herzegovina

Tuzla, Bosna i Hercegovina/Bosnia & Herzegovina

Zagreb, Hrvatska/Croatia

Novi Sad, Srbija/Serbia

Zagreb, Hrvatska/Croatia

Maribor, Slovenija/Slovenia

Sarajevo, Bosna i Hercegovina/ Bosnia & Herzegovina

Beograd, Srbija/Serbia

Skopje, Makedonija/Macedonia

Kassel, Njemačka/Germany

Skopje, Makedonija/Macedonia

Tuzla, Bosna i Hercegovina/ Bosnia & Herzegovina

Tuzla, Bosna i Hercegovina/ Bosnia & Herzegovina

Tuzla, Bosna i Hercegovina/ Bosnia & Herzegovina

Osijek, Hrvatska/Croatia

Sarajevo, Bosna i Hercegovina/ Bosnia & Herzegovina

Sarajevo, Bosna i Hercegovina/ Bosnia & Herzegovina

Osijek, Hrvatska/Croatia

Novi Sad, Srbija/Serbia

Skopje, Makedonija/Macedonia

Organizacioni Odbor/Organizing Committee

Prof. Dr. Kemal Gutić, Predsjednik/President

Prof. Dr. Ibrahim Čačković

Prof. Dr. Zijad Pašić

Prof. Dr. Sabid Zekan

Doc. Dr. Damir Zenunović

Doc. Dr. Nedim Suljić

Doc. Dr. Indira Sijerčić

Doc. Dr. Adnan Ibrahimović

SADRŽAJ/CONTENT

I DIO

Uvodna predavanja/Introductory Lecture

Dubravka Bjegović:	
ODRŽIVOST KAO STRATEGIJA U ISTRAŽIVANJIMA ARMIRANOG BETONA	3
Ivan Vrkljan:	
POLA STOLJEĆA MEHANIKE STIJENA KAO SAMOSTALNE ZNANSTVENE I INŽENJERSKE DISCIPLINE	29
Ludvik Trauner:	
THE CURRENT STATE AND TRENDS IN GEOTECHNICS	41
Mihailo D. Trifunac:	
EARTHQUAKE SPECTRA FOR PERFORMANCE BASED DESIGN	61

Tema 1: Istraživanja u polju materijala i njihove primjene Topic 1: Research in The Field of Materials and their Application

1.	A. Imamović, A. Džananović, Z. Begić, N. Rešidbegović: MOGUĆNOST PRIMJENE NEKIH OTPADNIH INDUSTRIJSKIH MATERIJALA PRI IZGRADNJI DONJEG STROJA SAOBRAČAJNICA	93
2.	A. Terzić, Lj. Pavlović, Lj. Miličić, Z. Radojević: CONSTRUCTION MATERIALS FOR HIGH TEMPERATURE APPLICATION BASED ON FLY ASH	103
3.	D. Jevtić, D. Zakić, A. Savić, A. Radević: EKSPERIMENTALNO ISPITIVANJE "ZELENIH" MALTERA SA RECIKLIRANIM GUMENIM AGREGATOM	111
4.	D. Sekulić, D. Bjegović, J. Bleiziffer: ODREĐIVANJE STANJA ARMIRANOBETONSKIH KONSTRUKCIJA IMPACT ECHO METODOM - PRIMJERI IZ PRAKSE	119
5.	I. Netinger, D. Bjegović, M. Jelić Rukavina, M. Serdar: UPORABA ČELIČANSKE ZGURE KAO AGREGATA U BETONU – HRVATSKA ISKUSTVA	127
6.	M. Malešev, V. Radonjanin, V. Milovanović, I. Likić: THE BASIC PROPERTIES OF STRUCTURAL LIGHTWEIGHT AGGREGATE CONCRETE DEPENDING TO THE TYPE AND AMOUNT OF CEMENT	135
7.	N. Ristić, Z. Grdić, G. Topličić Čurčić, I. Despotović: INFLUENCE OF ADDITION OF RECYCLED RUBBER TO CONCRETE ON ITS HYDRO-ABRASIVE RESISTANCE	145
8.	S. Juradin, A. Dretvić Halbärth, G. Baloević, A. Harapin: THE INFLUENCE OF SILICA FUME IN MORTAR COMPOSITION AND AS A PART OF THE CURING MEDIUM ON MECHANICAL PROPERTIES OF MORTAR	153
9.	S. Juradin, Ž. Čolić, G. Baloević, A. Harapin: ISPITIVANJE UTJECAJA VRSTE I KOLIČINE AGREGATA NA SVOJSTVA JEDNOZRNATOG I LAKOG BETONA	161
10.	V. Trifunović Dragišić, Z. Živković: BREAKAGE ISSUES IN SILICON SOLAR WAFERS AND SOLAR CELLS	169
11.	A. Kurtović: KOROZIJA CEMENTNOG BETONA	177
12.	A. Mirić, E. Vasić Petrović: MOGUĆNOSTI UPOTREBE SAVREMENIH POSTUPAKA I MATERIJALA ZA KONZERVACIJU BEDEMA I SPOMENIKA KULTURE UNUTAR NIŠKE TVRĐAVE	187
13.	D. Würth, J. Bleiziffer, K. Grubeša, S. Stefanović: POVRŠINA VIDLJIVOG BETONA IZVEDENA OD SAMOZBIJAJUĆEG BETONA	195
14.	P. Eliáš, M. Popenková: WORKABILITY OF INJECTION MATERIALS	203

Tema 2: Istraživanja i dostignuća u konstrukterstvu Topic 2: Research and Achievement in Structural Engineering

15.	A. Imamović, N. Rešidbegović, A. Džananović: OCJENA TRAJNOSTI BETONSKIH GRAVITACIONIH BRANA	211
16.	A. Mihanović, Ž. Nikolić, M. Kožul: NUMERIČKI MODEL ZA ANALIZU DEFORMACIJA PUZANJA BETONA U RAVNINI	219

17.	B. Milošević, Ž. Petrović, M. Mijalković: NOSIVOST RAMOVSKIH NOSAČA IZLOŽENIH DEJSTVU PROMENLJIVO PONOVLJENOG OPTEREĆENJA	227
18.	B. Popović: THE INFLUENCE OF THE REINFORCED CONCRETE BEAMS AXIAL FORCE ON THE SHAPE OF THE SHEAR FORCE-BENDING MOMENT INTERACTION DIAGRAM	235
19.	D. Markulak, I. Radić, V. Sigmund: ISPITIVANJE ČELIČNIH OKVIRA SA ZIDANIM ISPUNOM	243
20.	D. Nikolić, K. Janković, G. Čirković: TWO-LAYER RC BEAMS WITH PARTIAL USE OF UHPC	251
21.	D. Zenumović, E. Husejnjagić, R. Folić: APPLICATION OF GEO-ELECTRIC METHODS IN CIVIL STRUCTURES ASSESSMENT	259
22.	F. Casarin, M. Humo, F. da Porto, F. Lorenzoni, P. Girardello, C. Modena, L. Cantini, S. Kulukčija: NON-DESTRUCTIVE TESTING CAMPAIGN FOR TWO TRADITIONAL STONE MASONRY MINARETS IN BOSNIA AND HERZEGOVINA	267
23.	F.Vitalie: A STUDY OF BEHAVIOR OF A BRICK MASONRY WALL SUBJECTED TO LATERAL ACTIONS USING FINITE ELEMENTS METHOD	277
24.	F.Vitalie: A STUDY OF BEHAVIOR OF A BRICK MASONRY WALL SUBJECTED TO VERTICAL LOADS USING FINITE ELEMENTS METHOD	285
25.	H. Draganić, D. Markulak: EKSPERIMENTALNA I NUMERIČKA ANALIZA SPOJEVA S JEDNIM VIJKOM	293
26.	J. Šoltész, M. Ignačák, I. Binder: ASSEMENT OF THE HVAC PIPELINE SYSTEMS AT THE EMO34 NPP	301
27.	M. Lazarevska, M. Knezevic, M. Cvetkovska, A. Trombeva Gavriloska, T.Samardzioska: PROGNOZNO MODELIRANJE AB STUBOVA IZLOŽENE NA POŽAR PREKO NEURONSKE MREZE	309
28.	M. Memić, R. Folić: NUMERICAL MODELING AND ANALYSIS OF REINFORCED CONCRETE ANCHOR DIAPHRAGM WALLS	317
29.	M. Stanojev: INFLUENCE OF TEMPERATURE events AND SUPPORT SETTLEMENT IN INCREMENTAL LAUNCHING METHOD	329
30.	M. Tarić, E. Sadović, E. Maslak, H. Lukač: ANALIZA MODELIRANJA MOŽDANIKA KOD SPREGNUTIH KONSTRUKCIJA	337
31.	R. Folić, E. Sadović: RELIABILITY OF PRESTRESSED CONCRETE BRIDGE STRUCTURES	345
32.	S. Zdravković, D. Zlatkov, B. Mladenović, M. Stanojev: STABILITY OF SHELLS AS BEARING STRUCTURES FROM THE VIEW OF SAFETY	357
33.	V. Mirčevska, V. Bičkovski, K. Manova: ADAD-IZIIS SOFTWARE - OPTIONS AND SOME APPLICATION	365
34.	V. Vitanov : IMPLEMENTATION OF INELASTIC MODEL OF REINFORCED CONCRETE UNDER BIAXIAL MONOTONIC LOADING INTO ANSYS	373
35.	V. Vitanov: MODELING OF REINFORCED CONCRETE MEMBERS STRENGTHENED WITH FRP USING CUSTOM MATERIAL MODEL	381
36.	Y. Mihov, K. Russev: SHEAR REINFORCEMENT OF REINFORCED CONCRETE MEMBERS ACCORDING TO EUROCODE 2	389
37.	Z. Požegić, E. Mešić, B. Demirović, M. Toplaović: UTICAJ IMPERFEKCIJE NA GRANIČNO STANJE NOSIVOSTI I UPOTREBLJIVOSTI KOD SAČASTIH NOSAČA	399
38.	Ž. Petrović, B. Milošević, M. Mijalković: PRIMENA MATRIČNE ANALIZE KONSTRUKCIJA U ODREĐIVANJU GRANIČNOG OPTEREĆENJA KOD REŠETKASTIH NOSAČA	407
39.	A. Čilić, D. Đurić Mijović, J. Savić: GLOBAL STABILITY COMPARATIVE ANALYSIS OF MULTI-STORY STEEL BUILDING STRUCTURES RELATED TO DESIGNED JOINT CONNECTIONS AND STIFFENING SYSTEM	415
40.	C. Mojolic: PRELIMINARY STUDIES OF STRUCTURAL DESIGN OF THE GYMNASIUMS IN SFANTU- GHEORGHE AND SLATINA	421
41.	C. Mojolic: STRUCTURAL MODEL AND CONCEPTUAL OPTIMIZATION OF THE SFANTU- GHEORGHE MULTIFUNCTIONAL SPORT HALL ROOF	429
42.	I. Mekjavić, M. Marković: PRORAČUN CENTRA BUNDEK U ZAGREBU	435

43.	I.C. Muresan: A STUDY ON PLASTIC ANALYSIS AND OPTIMAL DESIGN OF STRUCTURES	443
44.	M. Spasojević Šurdulović, V. Prolović, N. Davidović: DESIGN SPECIFICITIES OF THE NEW BRIDGE OVER THE RIVER RAŠKA IN NOVI PAZAR	451
45.	Vlastimir Radonjanin, M. Malesev, Đ. Ladjinovic, I. Lukic, R. Okuka, V. Milovanović: REPAIR OF DAMAGED MASONRY BUILDINGS IN KRALJEVO AFTER EARTHQUAKE	457
46.	Ž. Tekić, S. Dorđević: DRVENA KONSTRUKCIJA KROVA U TEHNOLOGIJI LLD NAD OSNOVOM OBLIKA ZARUBLJENOG KVADRATA	465

Tema 3: Stanje i pravci razvoja u geotehnici

Topic 3: State and Trends in Geotechnics

47.	A. Antunović, D. Zovko: DOPRINOS GEOMEHANIČKOJ INTERPRETACIJI REZULTATA GEOELEKTRIČNIH ISPITIVANJA	475
48.	A. Ibrahimović, A. Babajić, E. Mandžić: KONCEPT ZAŠTITE I SANACIJE KOSINA USJEKA I ZASJEKA U FUNKCIJI OD POJAVNIH OBLIKA NESTABILNOSTI, UČESTALOSTI I MAGNITUDE NJIHOVOG POJAVLJIVANJA	483
49.	A. Jahić, D. Pašić Skripić, I. Žigić: KLIZIŠTA NA CESTAMA NASTALIM ANTROPOGENIM DJELOVANJEM U SLOŽENIM GEOLOŠKIM USLOVIMA	493
50.	A. Špago, M. Jovanovski, A. Ačkar: PRIMJENA GEOLOGICAL STRENGHT INDEX GSI – CLASSIFICATION ZA ANALIZU KARBONATNIH STIJENSKIH KOMPLEKSA	501
51.	B. Padovan, M. Maričić: MOGUĆNOSTI KORIŠTENJA VIŠEKANALNE ANALIZE POVRŠINSKIH VALOVA (MASW) PRI KLASIFIKACIJI TLA PREMA EUROKODU-8	509
52.	D. Berisavljević, N. Šušić, L. Čaki, K. Đoković: NUMERICAL ANALYSIS OF AXIALY LOADED PILE	517
53.	D. Petric: RESEARCH REGARDING THE SOIL-STRUCTURE INTERACTION EFFECTS ON DESIGN APPLICATIONS	525
54.	D. Petric: SOIL-STRUCTURE INTERACTION PROBLEMS ON CLASSICAL APPROCH AND FINITE ELEMENT METHOD	533
55.	D. Rakić, L. Čaki: THE IMPORTANCE OF GEOTECHNICAL DATA FOR DEEP EXCAVATION IN URBAN CENTRES	541
56.	G. Solovyov, A. Kasyanenko, R. Yastremskiy: STUDY OF FLOOR HEAVING IN THE MINE WORKING OF A COAL MINE BY MONITORING METHOD	549
57.	H. Begić, E. Ramović: KARAKTERISTIČNE ZONE KLIZIŠTA VISOKOG RIZIKA U FEDERACIJI BOSNE I HERCEGOVINE	557
58.	I. Bajrektarević, S. Zekan, M. Avdić, J. Malekin: TRODIMENZIONALNA ANALIZA STABILNOSTI KOSINA	569
59.	I. Molnar, A. Moldovan: MODELLING OF GEOTECHNICAL CHARACTERISTICS OF TRANSYLVANIAN SANDS	579
60.	I. Jašarevoć, M. Njegovec, H. Perković, H. Krhen: RACIONALNA SANACIJA KLIZIŠTA UZ PROMETNICE	587

II DIO

61.	J. Mesec, S. Strelec, J. Jug: OVISNOST INTENZITETA OSCILACIJA TLA PRILIKOM MINIRANJA O KOEFICIJENTU SVOJSTAVA STIJENE I NAČINA MINIRANJA K, I KOEFICIJENTU PRIGUŠENJA	599
62.	J. Papić, Lj. Dimitrievski, V. Prolović: VERIFICATION OF SELECTED DESIGN APPROACH AND PARTIAL FACTORS FOR SLOPE STABILITY ANALYSIS ACCORDING TO EC 7	607
63.	J. Savić, Z. Bonić, V. Prolović: MODERN TECHNOLOGIES OF FOUNDATION REMEDIATION IN THE PROCESS OF BUILDING REVITALIZATION	615

2nd International Scientific Meeting
GTZ 2012 & GEO-EXPO 2012
Tuzla, June 07-09, 2012

Gennady Solovyov¹
Andrey Kasyanenko²
Roman Yastremskiy³

**STUDY OF FLOOR HEAVING IN THE MINE WORKING OF A COAL MINE
BY MONITORING METHOD**

Summary: *The specific properties of the floor heave in condition of Abakumov Mine has been observed. Hard stratum floor has been discovered to be a major feature of floor heave. Results of this study have revealed that floor heave has occurred through four stages. They have been divided by features of floor movement and its deformation. It is established that floor heave occurs with a longitudinal asymmetry incurvation which vertical axis is tilted towards the goaf at an angle 35-50°.*

Key words: *Coal mine, Mine working, Floor heave, Instrumental observations, Monitoring method*

¹ Ass. Prof. Gennady I. Solovyov, Donetsk National Technical University, Faculty of Mining, Mineral Deposits Engineering, Artema 58, Donetsk, Ukraine, gisoloviev@gmail.com

² Graduate student Andrey L. Kasyanenko, Donetsk National Technical University, Faculty of Mining, Mineral Deposits Engineering, Artema 58, Donetsk, Ukraine, kasyanenkoal@gmail.com

³ Mining engineer Roman A. Yastremskiy, Chief engineer of Abakumov Mine of the state enterprise "Donetsk Coal Energy Company", Artema 63, Donetsk, Ukraine, yastremskiyra@gmail.com

1. INTRODUCTION

Abakumov Mine is a part of state enterprise “Donetsk Coal Energy Company”. In administrative terms, the mine is situated in Kirovsky Borough, Donetsk. The mining area is located in the western part of Donetsk and Makeyevka geologic industrial districts of the Donets Basin in Ukraine. The mining area of this property is 30 km²; the strike length is 8.5 km and 3.5 km to the dip.

Abakumov Mine is currently operating in the m_3 coalbed in the western flank of the mining area. The mine uses advancing and retreating longwall mining methods. Longwall panels are mined out by using fully mechanized system.

Nowadays mine is longwalling in the 8th western longwall m_3 coalbed. Working depth is about 860 m and a dip angle is 9°. The longwall panel is 1100 m long and 250 m wide (see Figure 1).




Figure 1. Plan of operation in the longwall area of Abakumov Mine

Drivage is carried out by drilling-and-blasting operations in advance of 5 m. Support system is used in entries of three-link yielding SVP-profile by steel strengthen support for every 0.5 m along the whole entry. Cross-section area is 16.1 m². A dirt-filled chock is 1.3 m in width and a hand-built dirt pack is 7.0 m in width were used to protect the entry.

Floor heave occurs in the belt entry of the 8th western longwall m_3 coalbed. When the entry is driven under high stress conditions, the cross-section area accelerates decreases. Basically, it happens on account of the floor heaving in quantity of 60% from convergence.

The amount of floor heaving was approximately 0.4-2.1 m along the whole entry. The miners had to dig out the heaving rock in the floor of the belt entry to keep it in order. In such a way this extra work is giving rise to financial problems and labour costs.

Generally, there are two reasons for floor heave. The first is the occurrence of high stresses within the floor rock [1] and the second is the loss of the floor rock strength [2].

The resulting floor heave usually causes various deformation and displacement such as breaks and heaves, producing numerous cracks [3]. In our case research it happens in condition of hard rocks which are adjacent to less hard immediate floor [4,5].

So, studies have been conducted to find out loss of strength of the floor rock for controlling floor heave in order not to be faced with the belt entry problem any more.

2. STRATIGRAPHIC RELATIONSHIPS

Throughout the longwall area, m_3 coalbed thickness averages from 0.9 to 1.0 m. The m_3 coalbed is medium-bright and uniaxial strength is 15-18 MPa.

The immediate roof is grey to dark-grey mudstone with lamination. Mudstone is generally from 7.0 to 10.3 m thick and the uniaxial strength is 30-40 MPa.

The immediate floor is dark-grey siltstone with uniaxial strength 40-60 MPa and its thickness is 1.2-1.6 m. Immediately beneath siltstone there is dark-grey to brown limestone, which uniaxial strength is 100-120 MPa and its thickness is 0.3-0.4 m.

Figure 2 is a generalized stratigraphic column of the interburden in the floor which contains hard rocks. Data of the geologic report of Abakumov Mine are used.




Figure 2. Generalized stratigraphic column

Thus, the stratigraphic column shows that the floor contains limestone and sandstone. Particularly they are adjacent to siltstone.

3. MONITORING METHOD

To establish a better understanding of extensive floor heave, three monitoring stations were built along the belt entry of the 8th western longwall m_3 coalbed. The monitoring stations are located by 10 m between them (see Figure 3).

The monitoring station has been consisted of six marks. The mark of wooden rod has length 0.4 m and diameter 0.03 m. Marks were installed in drilled shot holes in the centre roof of entry and in its sides at height of 2.5 m from floor. The rest of marks were

installed in the centre and sides of floor entry, so that their top has been located down at a distance of 0.05 m below the floor surface. On the end of each mark, a fixed steel hook is simply measured by a steel tape.




Figure 3. Layout of monitoring stations

Monitoring stations were used to measure the convergence in the height and width of the entry. A distance from the floor and roof marks to the midline (a line between side marks made by a steel tape) is schematically shown in Figure 4.




Figure 4. Marks measure scheme of monitoring stations in the belt entry

Measurements were carried out in series twice a week. At the same time, floor displacement was measured by using three floor marks. They were entry's goafside, centre and ribside.

Results were compared to choose the overall accuracy of the convergence between monitoring stations.

4. RESULTS OF MONITORING

The results of floor movement are given in Figure 5 in terms of displacement and its rate depend on the face distance. Calculation rate of displacement was adjusted taken into account the face advance by 50 meter per month.




Figure 5. Floor movement and its rate depending of face distance (a dotted line shows extrapolation data after ripping).

The graphs show that a floor movement increases in the rate of displacement along the face distance and slowdowns up to 35 m. The lifted floor is nonuniform in width peak of about: 2.5 m from a goafside; 1.8 m in the centre; 1.3 m from ribside.

It is necessary to notice that the ripping was carried out at a distance of 35 m from longwall face. Its size was 0.8-1.2 m for the half distance wide from entry's goafside, but the ripping was not made from entry's ribside. Three marks were repeatedly installed on floor.

5. ANALYSIS OF RESULTS

The results of monitoring made it possible to determine that the floor heave was carried out according to four stages.

At the first stage, some breaks and haves, producing numerous cracks were observed after the drivage of immediate floor. Floor displacement rate progressively increases nonuniformly along the entry wide. Thus, we have an inclination that increases up to 9° (fig. 6A). The completion of this stage means a cavity with break-up of the entry's goafside floor from face advance at a distance of 7 m (fig. 7A).

At the second stage the increasing rate of floor displacement from a goafside is established. There is an invariable in the centre and from a ribside as well. An angle of the floor inclination increases up 10° to 25° at this stage (fig. 6B). An intensive extrusion of the immediate floor (in some parts with break-ups) (fig. 7B) was observed on some sites starting from 7 to 25 m of face advance.

At the third stage (fig. 6C), there is a jumping rate of floor displacement from the face distance 25-35 m. Its maximum is 0.168 m/day. Thus, a view displacement of the floor stratum with creation of longitudinal asymmetry incurvation at a distance of 0.8-0.9 m from the goafside was observed (fig. 7C). Its vertical axis is tilted towards a goafside at an angle 35° - 50° . Floor displacement rate gradually decreased after the maximum achievement.

The fourth stage (fig. 6D) begins at about 35 m from face advance and the entry does not satisfy with safety rules. Thus, it is made with the help of ripping and retimbering where necessary (fig. 6E). After that, insignificant growth at a rate of floor displacement is stabilized.




Figure 6. Floor heave in stages (a dotted line shows a size before ripping)



A- 7 m from face advance



B - 14 m from face advance



C - 35 m from face advance

Figure 7. A photograph shows features of floor heave in Abakumov Mine

6. CONCLUSIONS

Results of this study in condition of Abakumov Mine were revealed that floor heave has occurred through four stages. They have been divided by features of floor movement and its deformation.

It is established that floor heave occurs with a longitudinal asymmetry incurvation which vertical axis is tilted towards the goaf at an angle 35-50°.

The adopted protection support methods at Abakumov Mine do not provide the belt entry of the 8th western longwall m₃ coalbed with stability.

Thus, it is more likely that the floor has to deform in order to establish hard rocks such as limestone and sandstone. It is unclear how a failure mechanism works in the floor structure to the extensive floor heave that results a hard stratum. In our opinion, it happens because of the anchorage between a pack and a hard stratum of limestone. Otherwise it would be hard to explain the cavity with break-up.

For better understanding, a further research will be focused on the reasons and developing protection support methods for controlling floor heave. Study will be carried out in order to keep the floor displacement in the acceptable limits in accordance with safety rules.

ACKNOWLEDGEMENTS

The authors wish to thank Ms. Darya Motorina, assistant, for support.

7. REFERENCES

1. Brady H.G., Brown E.T.: Rock Mechanics for underground mining, Kluwer Academic Publishers, Dordrecht, Netherlands, 2004, pages 626.
2. Seedsman R.W., Gordon N.: Weak claystone floors and their implications to pillar design and settlement, 11th International Conference on Ground Control in Mining, The University of Wollongong, Australia, 7-10 July 1992, pp. 548-555.
3. Yavuz M., Iphar M.: Evaluation of floor heaving in galleries by numerical analysis, 31st International Symposium on Application of Computers and Operations Research in the Minerals Industries, Cape Town, South Africa, 14-16 May 2003, pp. 185-189.
4. Chudek M., Соловьёв Г.И.: О проявлениях горного давления в выемочных выработках глубоких шахт Донбасса, IX Międzynarodowa Konferencja Szkoła Geomechaniki, Gliwice-Ustron, Poland, 20-23 October 2009, pp. 257-272.
5. Соловьёв Г.И., Касьяненко А.Л.: О механизме выдавливания прочных пород почвы глубоких шахт, XIV Międzynarodowe Sympozjum Geotechnika-Geotechnics, Gliwice-Ustron, Poland, 19-22 October 2010, pp. 253-262.